Perimeter Locations

Edgewater, New Jersey

	Sample Date	3/2/	2021	3/1/	2021	2/26	/2021	2/25/2021	2/24	/2021		2/23/2021			2/22/2021	
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD01	FD02	FD01	F	002	F	D01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24		24	2	24	24
	Average Wind Dir/Speed/Temp	NW/9.0	mph/33°F	WSW/3.6	mph/48°F	SSE/3.3	mph/46°F	NW/7.2 mph/49°F	NNE/2.1	mph/33°F		S/3.3 mph/55°F			SSW/3.2 mph/43°F	
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Duplicate	Primary
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	0.7	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.7	< 0.6	< 0.6	0.8	0.7	0.7	0.8	0.8	0.7
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	0.9	< 0.8	< 0.8	< 0.8	< 0.8	1	1	0.8	1	1	1	1	1	0.9
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		2/20/2021		2/19	/2021		2/18/2021			2/17/2021		2/16	/2021	2/12	/2021	2/11	1/2021
	Location ID	FI	D01	FD02	FD01	FD02	F	001	FD02	FD01	FC	002	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	:	24	24	24	24	2	24	24	24	2	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp		NW/6.1 mph/34°F		NNE/2.1	mph/33°F		ENE/2.6 mph/23°F			NW/4.8 mph/34°F		SW/3.7	mph/53°F	NNE/2.3	mph/29°F	N/2.4 n	nph/33°F
	Sample Type	Primary	Duplicate	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS	NS	NS	< 0.0088	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	0.8	0.8	0.7	0.8	0.8	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.7	0.7
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	0.9	0.8	0.8	0.8	0.9	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		2/10/2021		2/9/:	2021	2/8/	/2021	2/5/	2021	2/4/	2021	2/3/	2021	1/29/	2021	1/28	/2021
	Location ID	F	001	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	2	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp		NW/3.1 mph/36°F		NE/2.9 r	nph/33°F	WNW/3.9	9 mph/31°F	SW/3.3	mph/48°F	NW/5.3	mph/44°F	NW/4.5	mph/37°F	NW/9.3 i	nph/26°F	NNW/6.8	mph/34°F
	Sample Type	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	< 0.0088	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0081	NS	NS	NS	< 0.0085	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	0.8	0.8	0.8	0.7	1	0.9	1	0.9	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	0.9	0.9	0.8	0.8	2	1	2	2	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)

> - below analytical reporting limit (shown).

Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	1/27	/2021	1/26	5/2021		1/25/2021		1/22	2021	1/21	/2021	1/20	/2021	1/19.	/2021	1/18	3/2021
	Location ID	FD01	FD02	FD01	FD02	FD01	F	D02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	2	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	NW/5.1 i	mph/37°F	E/4.3 m	nph/34°F		N/2.1 mph/38°F		WSW/4.2	mph/45°F	SW/4.0 i	mph/44°F	WNW/6.1	mph/40°F	W/4.8 n	nph/42°F	W/4.9 r	mph/45°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0084	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	0.7	0.7	0.8	0.7	< 0.6	< 0.6	< 0.6	0.7	0.7	1	1	0.7	0.6	< 0.6	< 0.6	0.8	0.8
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.9	0.9	0.9	0.8	< 0.8	< 0.8	< 0.8	< 0.8	0.8	2	2	0.8	< 0.8	< 0.8	< 0.8	0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	1/15	5/2021		1/14/2021			1/13/2021		1/12	/2021	1/11	/2021	1/9/	2021	1/8/	/2021
	Location ID	FD01	FD02	FD01	FI	D02	F	001	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	:	24	2	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	E/4.7 n	nph/42°F		E/1.6 mph/49°F			SW/2.8 mph/43°F		NNW/2.6	mph/46°F	WNW/2.4	mph/36°F	NNW/3.9	mph/37°F	NNW/2.7	mph/37°F
	Sample Type	Primary	Primary	Primary	Primary	Duplicate	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0087	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	0.9	0.9	1	1	1	1	1	1	1	1	1	1	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.9	1	2	2	2	2	2	2	2	2	3	3	0.7	< 0.8	0.7	0.7
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	2	2	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	1/7/	/2021	1/6/	2021	1/5	/2021	1/4/	2021		12/24/2020		12/23	3/2020	12/22	2/2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	F	D01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	2	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	NNW/5.2	mph/43°F	NW/5.3	mph/41°F	NE/1.7	mph/41°F	NE/2.3 i	mph/42°F		SE/10.8 mph/57°F		SSW/2.3	mph/44°F	WNW/5.0	mph/46°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	NS	NS	NS	NS	< 0.0091	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0097	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.9	0.8	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		12/21/2020			12/19/2020		12/18	3/2020		12/15/2020		12/14	1/2020	12/11	1/2020	12/10/2020
	Location ID	FD01		002	FI	001	FD02	FD01	FD02	FD01		002	FD01	FD02	FD01	FD02	FD01
	Sample Exposure Time	24		24		24	24	24	24	24		24	24	24	24	24	24
	Average Wind Dir/Speed/Temp		WSW/2.2 mph/46°I	=		WNW/2.7 mph/31°l	F	NNW/3.1	mph/33°F		WNW/5.2 mph/40°	F	NNW/2.9	mph/41°F	SW/2.9	mph/56°F	WNW/5.2 mph/49°F
	Sample Type	Primary	Primary	Duplicate	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	< 0.0082	< 0.0082	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	1	1	1	1	NS	1	0.7	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	1	1	1
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	NS	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	2	2	2	1	NS	1	1	0.9	< 0.8	< 0.8	< 0.8	0.8	< 0.8	2	2	2
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	NS	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		12/9/2020			12/8/2020		12/7	/2020		12/4/2020			12/3/2020		12/2	2/2020
	Location ID	FD01	FC	002	FD01	FI	002	FD01	FD02	FD01	F	002	FD01	F	002	FD01	FD02
	Sample Exposure Time	24	2	24	24		24	24	24	24	2	24	24	2	24	24	24
	Average Wind Dir/Speed/Temp		SW/3.9 mph/37°F			NNW/4.9 mph/37°l	F	W/3.2 n	nph/41°F		SSW/3.1 mph/51°F	=		SW/3.8 mph/51°F		WSW/5.0	mph/44°F
	Sample Type	Primary	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	< 0.0090	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0088	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	0.7	0.6	0.7	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.9	0.8	0.9	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	1	1	1	0.9	0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		12/1/2020		11/30	0/2020		11/24/2020		11/23	3/2020	11/20	/2020		11/19/2020		11/18	3/2020
	Location ID	FD01	FC	002	FD01	FD02	FD01	FI	002	FD01	FD02	FD01	FD02	F	001	FD02	FD01	FD02
	Sample Exposure Time	24	2	24	24	24	24	:	24	24	24	24	24	2	24	24	24	24
	Average Wind Dir/Speed/Temp		SSW/4.8 mph/53°F		ESE/10.7	mph/62°F		WNW/4.1 mph/47°	F	NW/6.9	mph/58°F	SSW/3.3	mph/63°F		SSW/3.8 mph/48°F		NW/7.5	mph/37°F
	Sample Type	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS	NS	NS	< 0.0087	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0092	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.7	< 0.6	< 0.6	0.7	0.6	1	0.9	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.8	0.8	0.8	< 0.8	< 0.8	1	1	1	< 0.8	< 0.8	2	2	0.8	0.9	0.9	< 0.8	0.9
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	11/17	7/2020	11/16	6/2020	11/1	3/2020	11/12	2/2020		11/11/2020			11/10/2020		11/9	9/2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	F	D01	FD02	FD01	F	002	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	2	24	24	24	2	24	24	24
	Average Wind Dir/Speed/Temp	WNW/4.3	3 mph/49°F	W/6.1 n	nph/53°F	SE/2.0	mph/66°F	NNW/3.3	mph/66°F		S/2.3 mph/70°F			SSW/3.4 mph/74°F		SSE/1.9	mph/77°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Duplicate	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0088	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	0.7	0.7	0.8	0.8	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	2	2
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	1	< 1	< 1	< 1	1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	1	1	2	2	< 0.8	< 0.8	1	1	1	2	1	1	3	4
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	3	3

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		11/6/2020		11/5	/2020	11/4	/2020	11/3	/2020	11/2	2/2020	10/3	1/2020	10/30	0/2020
	Location ID	FD01	F	002	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	2	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp		S/2.7 mph/72°F		S/2.9 m	nph/69°F	SE/2.0 i	mph/66°F	W/6.5 n	nph/54°F	WNW/9.4	1 mph/45°F	SW/3.1	mph/48°F	NNW/3.7	mph/44°F
	Sample Type	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	< 0.0086	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	1	1	1	0.9	1	0.8	0.8	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	2	2	2	2	2	1	2	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		10/29/2020		10/2	3/2020	10/27	7/2020	10/26	6/2020		10/23/2020		10/22	2/2020	10/21	1/2020
	Location ID	FD01	FC	002	FD01	FD02	FD01	FD02	FD01	FD02	FI	D01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	2	24	24	24	24	24	24	24		24	24	24	24	24	24
	Average Wind Dir/Speed/Temp		E/3.0 mph/54°F		NNW/2.1	mph/58°F	N/2.2 m	ph/60°F	ENE/2.4	mph/58°F		SSE/2.1 mph/69°F		E/1.0 m	ph/69°F	SE/2.5 n	nph/73°F
	Sample Type	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0098	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	0.7	0.6	< 0.6	< 0.6	0.8	0.8	< 0.6	< 0.6	< 0.6	0.7	0.7	1	1
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.8	< 0.8	< 0.8	2	1	1	0.9	2	2	1	2	1	2	2	3	3
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	2	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	10/20	0/2020		10/19/2020		10/17	7/2020	10/16	6/2020	10/1	5/2020		10/14/2020		10/13	3/2020
	Location ID	FD01	FD02	FI	D01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	F	002	FD01	FD02
	Sample Exposure Time	24	24		24	24	24	24	24	24	24	24	24		24	24	24
	Average Wind Dir/Speed/Temp	SE/2.5 r	mph/72°F		ESE/3.1 mph/66°F		NW/4.7	mph/61°F	NW/3.3	mph/64°F	S/4.4 n	nph/74°F		SW/3.3 mph/70°F		N/3.6 n	nph/60°F
	Sample Type	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0095	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	1	1	< 0.6	< 0.6	< 0.6	< 0.6	0.8	0.7	0.7	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	1	< 1	2	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	1	2	1	1	2	2	0.8	0.9	0.8	1	2	2	2	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	10/12	2/2020	10/9	/2020	10/8	3/2020		10/7/2020		10/6	/2020	10/5	/2020	10/2	2/2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	F	002	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	2	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	E/4.3 n	nph/55°F	SSE/2.2	mph/68°F	WNW/6.3	mph/65°F		SW/4.6 mph/76°F		SW/3.5	mph/71°F	E/3.1 m	nph/71°F	W/3.3 n	mph/66°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0085	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	0.8	< 0.8	< 0.8	< 0.8	1	1
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		10/1/2020		9/30	/2020		9/29/2020			9/28/2020		9/25	/2020		9/24/2020	
	Location ID	FD01	FC	002	FD01	FD02	F	D01	FD02	F	D01	FD02	FD01	FD02	FD01	F	002
	Sample Exposure Time	24	2	24	24	24	2	24	24	2	24	24	24	24	24	2	24
	Average Wind Dir/Speed/Temp		WSW/3.8 mph/73°F	-	WSW/5.3	mph/71°F		SSE/3.0 mph/75°F			S/4.0 mph/81°F		S/2.6 m	ph/78°F		SSW/2.1 mph/77°F	=
	Sample Type	Primary	Primary	Duplicate	Primary	Primary	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Duplicate
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.8	0.8	0.8	0.9	0.9
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	0.9	< 0.8	< 0.8	< 0.8	< 0.8	2	2	2	2	2
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	9/23/	/2020	9/22/	2020	9/21	/2020	9/19	9/2020	9/18	2020	9/17	/2020	9/16	/2020		9/15/2020	
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	F[	D02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	2	24
	Average Wind Dir/Speed/Temp	WNW/5.7	mph/81°F	NNW/3.9	mph/74°F	ENE/2.7	mph/69°F	NNE/3.3	mph/65°F	N/3.5 m	iph/71°F	SW/2.6	mph/76°F	SSW/3.3	mph/73°F		NE/2.4 mph/69°F	
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	< 0.0086	NS	NS	NS	< 0.0088	< 0.0090	NS								
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	0.8	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	1	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	1	1	0.9	0.9	1	1	1
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	2	3	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	9/14	/2020	9/11/	/2020		9/10/2020		9/9/	/2020		9/8/2020		9/3/	2020	9/2/	2020
	Location ID	FD01	FD02	FD01	FD02	FI	001	FD02	FD01	FD02	FD01	F	002	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24		24	24	24	24	24	2	24	24	24	24	24
	Average Wind Dir/Speed/Temp	NW/4.6	mph/76°F	N/2.7 m	nph/78°F		SE/2.7 mph/84°F		E/1.9 n	nph/84°F		SE/2.3 mph/84°F		WNW/2.7	mph/88°F	SE/2.9 r	mph/82°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	< 0.0089	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	1	1	0.9	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	0.9	1	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	0.9	1	1	1	1	1	2	2	2	1	0.9	0.8	0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	2	< 0.9	4	5	< 0.9	< 0.9	< 0.9	4

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		9/1/2020			8/31/2020		8/28	/2020	8/27/	/2020	8/26/2020	8/25	/2020	8/24	1/2020
	Location ID	FI	D01	FD02	FI	001	FD02	FD01	FD02	FD01	FD02	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time		24	24	1	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp		ESE/2.8 mph/79°F			E/2.1 mph/78°F		W/4.3 n	nph/88°F	SW/3.8 r	mph/93°F	NW/6.7 mph/79°F	W/5.1 n	nph/90°F	SW/3.7	mph/92°F
	Sample Type	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	< 0.0091	NS	NS	NS	NS	NS	NS	NS	< 0.0089	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	2	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	3	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	1	0.9	0.9	< 0.8	< 0.8	< 0.8	1	0.9
Xylenes, Total	104	< 0.9	< 0.9	9	< 0.9	< 0.9	4	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		8/22/2020		8/21	/2020		8/20/2020		8/19	/2020	8/18	/2020	8/17	/2020	8/14	/2020
	Location ID	FD01	FC	002	FD01	FD02	FD01	FC	002	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	2	24	24	24	24	2	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp		W/4.6 mph/94°F		WSW/4.4	mph/96°F		W/4.6 mph/94°F		ENE/1.8	mph/75°F	W/3.4 n	nph/84°F	S/3.9 m	ph/82°F	E/3.6 m	nph/88°F
	Sample Type	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0087	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	0.7	1	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	1	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	1	1	3	< 1	< 1	1	1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	2	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.9	1	1	1	1	0.9	1	0.9	1	1	1	1	< 0.8	0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	3	2	2	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		8/13/2020		8/12	2/2020		8/11/2020		8/10	/2020	8/8/	2020	8/7/	2020	8/6/	/2020
	Location ID	FI	D01	FD02	FD01	FD02	F	001	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	:	24	24	24	24	2	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp		NE/1.6 mph/80°F		E/2.9 n	nph/92°F		SSE/6.2 mph/90°F		S/3.7 m	nph/93°F	NE/1.6 i	nph/83°F	W/4.0 n	nph/88°F	E/2.7 m	nph/83°F
	Sample Type	Primary	Duplicate	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	< 0.0090	< 0.0087	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0090	NS
1,2,4-Trimethylbenzene	62.6	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	NS	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	NS	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	NS	1	1	0.9	0.8	0.9	< 0.8	0.9	0.8	< 0.8	< 0.8	1	1	1	1
Xylenes, Total	104	< 0.9	NS	< 0.9	< 0.9	2	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	2

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	8/5/	2020		8/3/2020		7/31.	/2020	7/30	2020	7/29	/2020		7/28/2020		7/27	7/2020
	Location ID	FD01	FD02	F	001	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	F	002	FD01	FD02
	Sample Exposure Time	24	24	:	24	24	24	24	24	24	24	24	24	2	24	24	24
	Average Wind Dir/Speed/Temp	W/4.0 r	mph/88°F		WSW/4.6 mph/91°	F	ESE/2.1	mph/81°F	WSW/3.8	mph/93°F	SSE/3.8	mph/90°F		W/4.6 mph/94°F		WSW/4.4	1 mph/96°F
	Sample Type	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	< 0.0085	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	0.7	< 0.6	< 0.6	< 0.6	< 0.6	0.9	< 0.6	< 0.6	< 0.6	1	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	2	< 1	1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	1	< 0.8	< 0.8	1	2	3	1	1	1	3	0.9	< 0.8	1	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	2	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	7/24	/2020	7/23	/2020		7/22/2020			7/21/2020		7/20	/2020	7/18	/2020	7/17	//2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FC	002	F	D01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	2	24		24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	ENE/2.9	mph/79°F	SE/3.3 r	mph/93°F		SE/3.3 mph/93°F			SSE/3.6 mph/92°F		W/4.5 n	nph/96°F	E/2.9 n	nph/93°F	SSE/3.8	mph/84°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	< 0.0086	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	2	< 1	1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	1	< 1	1	2	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	2	2	< 0.8	< 0.8	0.9	0.9	0.8	1	1	0.9	0.8	1	< 0.8	1	1	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		7/16/2020			7/15/2020		7/14	/2020	7/13	/2020		7/11/2020		7/10	/2020
	Location ID	FC	001	FD02	FD01	F	002	FD01	FD02	FD01	FD02	F	001	FD02	FD01	FD02
	Sample Exposure Time	2	24	24	24	2	24	24	24	24	24	2	24	24	24	24
	Average Wind Dir/Speed/Temp		SE/6.2 mph/78°F			E/3.9 mph/84°F		NW/5.0	mph/88°F	WNW/4.3	mph/88°F		S/3.6 mph/85°F		E/5.4 m	nph/78°F
	Sample Type	Primary	Duplicate	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	NS	NS	NS	< 0.0090	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	1	< 1	< 1	< 1	< 1	< 1	< 1	2	< 1	4	2	< 1	< 1	2	1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	1	< 0.8	0.9	< 0.8	0.9	< 0.8	1	1	0.9	0.8	< 0.8	< 0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)

> - below analytical reporting limit (shown).

Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	1													
	Sample Date		7/9/2020			7/8/2020		7/7/2	2020		7/6/2020			/2020
	Location ID	F	D01	FD02	FD01	F	002	FD01	FD02	FE	001	FD02	FD01	FD02
	Sample Exposure Time	2	24	24	24	2	24	24	24	2	4	24	24	24
	Average Wind Dir/Speed/Temp		SSE/4.7 mph/89°F			S/3.7 mph/78°F		ESE/4.1	mph/82°F		SE/3.4 mph/95°F		NNW/2.9	mph/93°F
	Sample Type	Primary	Duplicate	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary
Analyte	Risk Screening Level													
	24-hour exposure													
Arsenic	0.037	< 0.0086	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	2	2	3	2	3	2	< 1	< 1	< 1	< 1	< 1	< 1	2
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	0.8	1	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	0.9	0.9
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)

> - below analytical reporting limit (shown).

Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		7/1/2020		6/30	/2020	6/29	/2020	6/26	5/2020	6/25	/2020	6/24	/2020		6/23/2020	
	Location ID	FD01	T FC	102	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FI	001	FD02
	Sample Exposure Time	24	2	04	24	24	24	24	24	24	24	24	24	24		24	24
	Average Wind Dir/Speed/Temp	27	SE/2.9 mph/81°F			nph/80°F		mph/92°F		2 mph/88°F		nph/86°F	W/5.4 m	nnh/88°F	1	SSE/5.6 mph/86°F	
	Sample Type	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary
Analyte	Risk Screening Level									1							
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	< 0.0090	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	4	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.8	0.9	< 0.8	1	1	< 0.8	< 0.8	1	2	4	1	< 0.8	< 0.8	0.9	0.9	1
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	6/22	/2020	6/20/	/2020	6/19	/2020	6/18	1/2020	6/17	7/2020	6/16	/2020	6/15	/2020		6/12/2020	
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FE	001	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	2	24	24
	Average Wind Dir/Speed/Temp	S/3.9 m	ph/91°F	SE/3.1 n	nph/66°F	SSE/4.2	mph/86°F	SE/3.1	mph/80°F	ESE/4.1	mph/80°F	E/4.1 m	nph/79°F	E/3.2 m	iph/77°F		WNW/4.3 mph/86°l	-
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.9	< 0.8	1	< 0.8	1	1	0.9	1	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	6/11	/2020		6/10/2020		6/9/	2020	6/8/	2020	6/5/	2020	6/4/	2020	6/3/	/2020
	Location ID	FD01	FD02	FD01	F	002	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	2	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	SSW/4.5	mph/83°F		ESE/4.6 mph/85°F		SSW/4.0	mph/89°F	NW/3.5 i	mph/82°F	SW/3.3	mph/81°F	SSW/3.3	mph/85°F	SSW/3.6	mph/79°F
	Sample Type	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	NS	NS	NS	NS	NS	< 0.0091	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	1	< 1	< 1	< 1	1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	2	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	0.8	< 0.8	0.8	< 0.8	0.9	0.8	1	1	0.8	0.9	0.8	0.8	0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		6/2/2020		6/1/	2020		5/29/2020			5/28/2020			5/27/2020			5/26/2020	
	Location ID	FD01	F	002	FD01	FD02	FD01	FI	D02	FI	D01	FD02	FE	001	FD02	F	001	FD02
	Sample Exposure Time	24	2	24	24	24	24		24	:	24	24	2	24	24	2	24	24
	Average Wind Dir/Speed/Temp		SW/3.6 mph/74°F		WNW/4.7	mph/71°F		S/3.9 mph/81°F			SE/4.1 mph/76°F			SSE/4.0 mph/78°F			SSE/3.7 mph/75°F	
	Sample Type	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Duplicate	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Primary	Duplicate	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	< 0.0085	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0085	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	1	1	< 1	< 1	1	2	1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	2	0.9	0.9	0.8	0.9	0.8	0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)

> - below analytical reporting limit (shown).

Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	5/22	/2020	5/21/	2020	5/20	/2020	5/19	/2020	5/18	/2020	5/15	/2020		5/14/2020		5/13	3/2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	F	001	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	2	24	24	24	24
	Average Wind Dir/Speed/Temp	SSE/3.1	mph/73°F	SE/3.1 n	nph/66°F	E/4.3 n	nph/67°F	E/6.6 n	nph/67°F	E/3.3 n	nph/71°F	SSW/4.6	mph/86°F		SE/4.2 mph/65°F		WNW/4.8	8 mph/63°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS	NS	< 0.0088	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.8	0.7	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	1	1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	2	2	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	< 0.8	2	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	1	1	< 0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	2	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	5/12	/2020	5/11/	/2020	5/8/	2020	5/7/	2020	5/6/	2020	5/5/	2020	5/4/	2020	5/1/	/2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	NW/7.5	mph/61°F	WSW/3.6	mph/61°F	NW/2.5	mph/55°F	NW/5.5	mph/66°F	E/4.1 m	nph/51°F	NW/5.6	mph/63°F	NW/4.8	mph/72°F	SE/2.4 i	mph/64°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	< 0.0091	NS	NS	NS	NS	NS	NS	NS	< 0.0082	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	4/30	)/2020		4/29/2020		4/28	/2020	4/27	7/2020	4/24	/2020		4/23/2020		4/22	2/2020
	Location ID	FD01	FD02	F	001	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	F	002	FD01	FD02
	Sample Exposure Time	24	24	2	24	24	24	24	24	24	24	24	24	2	24	24	24
	Average Wind Dir/Speed/Temp	SE/12.0	mph/60°F		E/4.4 mph/57°F		NW/4.7	mph/65°F	NNW/3.1	mph/49°F	NE/2.1 i	mph/50°F		W/2.1 mph/49°F		WNW/8.2	2 mph/49°F
	Sample Type	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	< 0.0085	NS	NS	NS	NS	NS	< 0.0090	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	4/21	/2020		4/20/2020		4/18	3/2020	4/17	2020	4/16	/2020	4/15	/2020	4/14/	2020	4/13	3/2020
	Location ID	FD01	FD02	FD	001	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	2	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	SSW/4.6	mph/59°F		NNE/2.7 mph/56°F		N/2.6 n	nph/45°F	WSW/4.4	mph/50°F	NW/8.1	mph/48°F	NW/5.1	mph/53°F	NW/4.6 r	mph/59°F	SSE/11.7	mph/58°F
	Sample Type	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0089	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	4/10	/2020	4/9/	2020	4/8/	2020	4/7/:	2020	4/6/	2020	4/3/	2020	4/2/	2020	4/1/:	/2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	WNW/7.8	mph/48°F	SSE/5.8	mph/58°F	E/2.0 n	nph/64°F	SW/4.1 i	nph/64°F	ENE/3.4	mph/67°F	NNW/5.8	mph/52°F	NNW/7.6	mph/58°F	NE/3.5 r	mph/57°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
•	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	NS	< 0.0093	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	2	< 1	< 1	3	2	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	0.8	0.8	1	1	< 0.8	< 0.8	< 0.8	< 0.8	0.9	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	3/31.	/2020	3/30/	2020	3/27	7/2020	3/26	6/2020	3/25	/2020	3/24	/2020	3/23	/2020		3/20/2020	
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FI	D02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24		24
	Average Wind Dir/Speed/Temp	E/3.3 m	ph/49°F	ESE/2.1	mph/51°F	ESE/3.5	mph/67°F	SE/3.3	mph/59°F	E/4.5 n	nph/45°F	NE/3.5 r	mph/54°F	E/5.0 m	ph/39°F		SSE/2.9 mph/62°F	
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	< 0.0089	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0087	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	0.7	< 0.6	0.8	< 0.6	0.8	< 0.6	1	< 0.6	< 0.6	< 0.6	0.7	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	2	< 1	2	< 1	7	< 1	1	< 1	6	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	< 0.8	< 0.8	0.8	< 0.8	1	0.8	0.9	< 0.8	2	< 0.8	< 0.8	< 0.8	2	0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)

> - below analytical reporting limit (shown).

Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	3/19	/2020	3/18	2020	3/17/2020	3/16	/2020	3/13	/2020		3/12/2020		3/11	/2020	3/10	)/2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FD01	FD02	FD01	FD02	FI	D01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24		24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	E/2.1 m	nph/50°F	S/3.4 m	ph/53°F	SE/2.5 mph/54°F	ESE/3.3	mph/47°F	S/4.7 n	nph/70°F		E/2.2 mph/50°F		E/2.7 m	ph/60°F	SSW/5.1	mph/65°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	< 0.0090	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0090	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	2	1	< 1	< 1	< 1	< 1	< 1	< 1	1	< 1	2	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	1	< 0.6	4	7	< 0.6	< 0.6	< 0.6	0.7	0.7	< 0.6	2	0.9	3	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	2	2	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	1	< 0.9	3	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	2	2	< 1	< 1	< 1	< 1	< 1	< 1	2	< 1	24	2
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	0.8	2	< 0.8	8	13	< 0.8	< 0.8	< 0.8	1	1	0.9	4	1	3	0.9
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	9	11	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	5	< 0.9	7	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	3/9/2	2020	3/6/2	2020	3/4/	2020		3/3/2020		3/2/	2020	2/28/	/2020	2/27/	2020	2/26	2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	F	01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	2	4	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	SSW/3.9	mph/78°F	E/3.0 m	ph/45°F	W/7.3 n	nph/57°F		SE/3.9 mph/57°F		SSE/4.5	mph/58°F	WSW/6.0	mph/42°F	W/8.6 m	nph/42°F	E/1.8 m	ph/47°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS	NS	NS	NS	< 0.0091	NS	NS	NS	NS	NS	NS	< 0.0091	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	3	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	1	0.6	1	< 0.6	4	< 0.6	0.6	0.6	< 0.6	0.8	0.7	< 0.6	0.7	< 0.6	< 0.6	0.8	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	4	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	32	5	1	1	< 1	10	2	< 1	< 1	< 1	2	1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	2	1	2	< 0.8	8	0.8	1	1	0.8	2	0.9	< 0.8	0.8	< 0.8	< 0.8	3	0.9
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	12	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	2/24	1/2020	2/21	/2020	2/20	)/2020	2/19	/2020		2/18/2020			2/14/2020		2/13	3/2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	F	001	FD02	F	D01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	2	24	24	2	24	24	24	24
	Average Wind Dir/Speed/Temp	SSE/3.6	mph/60°F	N/2.7 m	nph/37°F	WNW/4.4	4 mph/35°F	NW/6.9	mph/48°F		E/2.8 mph/46°F			NW/7.7 mph/31°F		W/2.0 n	mph/42°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	< 0.0091	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	0.7	0.7	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.7	0.9	0.8	< 0.6	< 0.6	< 0.6	0.8	0.8
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	2	2	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	0.9	1	1	< 0.8	< 0.8	< 0.8	1	1
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	2/12	2/2020	2/11	/2020	2/10	/2020	2/7/	2020	2/6/	2020	2/5/	2020	2/4/	2020	2/3/	2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	W/3.8 n	mph/46°F	ENE/1.2	mph/47°F	SW/4.5	mph/47°F	WNW/5.6	mph/56°F	E/3.0 m	ph/41°F	NE/2.1 r	nph/43°F	SSE/2.2	mph/55°F	SW/3.7	mph/58°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	< 0.0090	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0091	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	0.8	0.7	0.6	< 0.6	< 0.6	< 0.6	0.8	< 0.6	< 0.6	< 0.6	1	1	1	1
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	2	2	2	2
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	1	1	2	1	1	< 0.8	1	< 0.8	< 0.8	< 0.8	3	2	2	2
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	2	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		1/31/2020			1/30/2020		1/29	9/2020	1/28	/2020	1/27	/2020		1/24/2020		1/23	3/2020
	Location ID	FC	001	FD02	FD01	F	D02	FD01	FD02	FD01	FD02	FD01	FD02	F	001	FD02	FD01	FD02
	Sample Exposure Time	2	24	24	24		24	24	24	24	24	24	24	2	24	24	24	24
	Average Wind Dir/Speed/Temp		ENE/1.0 mph/42°F			ENE/2.0 mph/38°l	=	NNW/4.7	mph/43°F	NW/5.8	mph/43°F	SW/4.4	mph/46°F		E/1.7 mph/53°F		S/2.5 n	mph/45°F
	Sample Type	Primary	Duplicate	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS	< 0.0090	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	1	1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	1	1	1	0.9	0.8	0.8	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	1	1	1	2	2
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	1	0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	4	3
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	2	1	2	1	1	1	< 0.8	< 0.8	< 0.8	< 0.8	0.8	0.9	2	2	2	4	6
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	4	4

## Notes:

All data shown in micrograms per cubic meter (µg/m³)

> - below analytical reporting limit (shown).

Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	1/22	2/2020	1/21	/2020	1/20	/2020	1/17	/2020	1/16	/2020		1/15/2020		1/14	/2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FI	001	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	:	24	24	24	24
	Average Wind Dir/Speed/Temp	SW/2.8	mph/41°F	N/2.8 m	nph/35°F	NNW/5.6	mph/33°F	ENE/2.8	mph/34°F	WNW/7.8	mph/49°F		WNW/3.9 mph/51°F		E/2.0 m	nph/45°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	< 0.0090	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0089	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	1	1	0.7	0.7	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	1	1	1	1	1
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	2	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	1	2	< 1	< 1	1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	3	4	1	1	< 0.8	< 0.8	< 0.8	< 0.8	0.8	< 0.8	2	2	2	2	2
Xylenes, Total	104	2	4	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	1/13	3/2020	1/10	/2020	1/9	2020	1/8/	2020	1/7/	2020	1/6/	2020	1/3/	2020	1/2/	2020
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	E/1.4 n	nph/44°F	SW/4.0	mph/55°F	N/3.3 r	nph/35°F	W/5.8 n	nph/44°F	ESE/2.2	mph/46°F	SW/4.4	mph/45°F	S/2.1 m	nph/47°F	SSW/2.9	mph/49°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	< 0.0089	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0089	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	1	1	0.9	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.9	0.8	< 0.6	< 0.6	2	2	1	1
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	1	6	1	1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	2	2	2	1	0.8	0.8	< 0.8	< 0.8	1	1	< 0.8	< 0.8	3	3	2	2
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	2	4	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	12/31	12019	12/30	0/2019	12/20	)/2019	12/19	9/2019	12/18	/2019	12/17	7/2019	12/16	6/2019
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	NW/2.1 i	mph/40°F	E/7.3 n	nph/41°F	NW/4.8	mph/27°F	WNW/7.6	mph/26°F	WSW/3.9	mph/36°F	ENE/3.0	mph/34°F	WNW/2.4	mph/36°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level														
	24-hour exposure														
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0088	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	0.6	0.7	< 0.6	0.6	0.7	0.8	< 0.6	< 0.6	< 0.6	< 0.6	0.7	0.7	0.8	0.7
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.9	1	< 0.8	< 0.8	< 0.8	0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	1	1
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	12/13	3/2019	12/12	2/2019	12/1	1/2019	12/10	0/2019	12/9/	2019	12/6	/2019	12/5	/2019	12/4	/2019
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
A	Average Wind Dir/Speed/Temp	ENE/1.5	mph/44°F	N/3.2 m	nph/38°F	WNW/2.2	2 mph/38°F	SW/3.8	mph/58°F	SE/2.1 n	nph/52°F	SSW/3.9	mph/49°F	W/6.2 n	nph/42°F	SW/2.8	mph/38°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
-	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0091	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	1	1	0.7	0.9	0.7	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.8	0.7
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	1	0.9	1	< 0.8	< 0.8	0.8	0.9	0.8	0.8	1	1	< 0.8	< 0.8	1	1
(ylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	12/3	3/2019	12/2	/2019	11/2	7/2019	11/26	6/2019	11/25	5/2019	11/21	/2019	11/20	0/2019	11/19	9/2019
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	NW/6.5	mph/37°F	NNW/3.9	mph/36°F	SE/2.0	mph/58°F	SSW/2.9	mph/61°F	SSW/2.9	mph/54°F	NW/2.5	mph/55°F	NNW/4.5	mph/50°F	WNW/3.6	mph/47°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	NS	< 0.0091	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.7	1	1	1	< 0.6	< 0.6	< 0.6	0.7	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	3	7	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.9	0.8	< 0.8	< 0.8	2	2	4	4	1	< 0.8	0.8	0.8	1	0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	3	4	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	11/18	3/2019	11/15	5/2019	11/1-	1/2019	11/13	3/2019	11/12	2/2019	11/11	/2019	11/8	/2019	11/7	7/2019
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	NNW/2.6	mph/42°F	SW/3.4 i	mph/52°F	SW/3.2	mph/44°F	NW/6.7	mph/40°F	NW/6.6	mph/54°F	SE/1.4 r	nph/61°F	NW/6.7	mph/40°F	SW/3.5	mph/57°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0090	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	0.7	0.8	< 0.6	< 0.6	< 0.6	< 0.6	0.7	0.7	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.9	0.8	2	1	2	2	0.8	< 0.8	< 0.8	< 0.8	2	2	< 0.8	< 0.8	1	0.9
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	11/6/	/2019		11/5/2019		11/4	/2019	11/1	2019	10/31	1/2019	10/30	)/2019	10/29	/2019	10/28	3/2019
	Location ID	FD01	FD02	FD01	FE	002	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	2	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	W/3.9 m	nph/57°F		WSW/2.2 mph/61°F	=	SSW/3.9	mph/57°F	W/6.6 n	ph/57°F	SSW/5.1	mph/72°F	ENE/1.0	mph/63°F	E/1.7 m	ph/59°F	NE/1.8 r	mph/63°F
	Sample Type	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	< 0.0090	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	0.6	< 0.6	0.8	0.7	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	2
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	1	1	1	1	0.8	0.9	< 0.8	< 0.8	< 0.8	< 0.8	1	1	1	1	0.9	0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	10/25	5/2019	10/24	/2019	10/23	3/2019	10/2:	2/2019	10/2	1/2019	10/18	3/2019	10/17	7/2019		10/16/2019	
	Location ID	FD01	FD02	F	001	FD02												
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	2	24	24
	Average Wind Dir/Speed/Temp	SSW/2.6	mph/66°F	SSW/3.0	mph/68°F	W/4.9 n	nph/67°F	E/3.1 n	nph/60°F	ENE/2.4	mph/71°F	NW/6.6	mph/59°F	WSW/6.9	mph/58°F		ESE/6.2 mph/66°F	
	Sample Type	Primary	Primary	Primary	Duplicate	Primary												
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS														
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	0.8	0.8	0.8	0.7	0.9	1	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	1	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	2	1	< 1	1	2	1	< 1	1	2	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	2	3	2	2	2	2	1	2	2	2	1	0.9	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8
Xylenes, Total	104	2	2	2	< 0.9	2	3	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	10/15	5/2019	10/14	1/2019	10/11	1/2019	10/10	/2019	10/9/	2019	10/8	/2019	10/7	//2019
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	N/3.1 m	ph/67°F	WSW/3.9	mph/75°F	NNE/3.6	mph/66°F	N/3.5 m	ph/71°F	NE/3.3 r	nph/59°F	NNE/2.4	mph/64°F	SSW/4.6	mph/79°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level														
	24-hour exposure														
Arsenic	0.037	< 0.0089	NS	NS	NS	NS	NS	NS	NS	< 0.0089	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	1	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	1	< 1	1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	1	1	1	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	0.8	< 0.8	2	< 0.8	0.9
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)

> - below analytical reporting limit (shown).

Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	10/4	/2019	10/3	/2019	10/2	/2019	10/1	/2019	9/30	/2019	9/27	/2019	9/26	/2019	9/25	/2019
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	NW/5.7	mph/66°F	E/3.9 m	ph/56°F	WSW/4.3	mph/94°F	SSW/4.4	mph/81°F	ESE/2.8	mph/73°F	SSE/3.1	mph/76°F	SSW/4.2	mph/82°F	W/3.3 n	nph/80°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	< 0.0087	NS	NS	NS								
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	1	0.9	0.9	0.8	0.9	1	2	0.8	< 0.8	0.9	0.9	2	2	2	2
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	9/24	/2019	9/23/	/2019	9/20	/2019	9/19	/2019	9/18	/2019	9/17	/2019	9/16	/2019	9/13	3/2019
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02								
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	WNW/5.3	mph/78°F	SSW/4.0	mph/89°F	W/3.7 r	nph/80°F	ESE/2.7	mph/73°F	ENE/2.5	mph/72°F	ENE/2.8	mph/80°F	E/2.0 m	ph/79°F	ESE/3.9	mph/72°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary								
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	< 0.0085	NS	NS	NS	NS	NS								
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	0.6	0.7	< 0.6	< 0.6	< 0.6	< 0.6	0.6	< 0.6	< 0.6	< 0.6	0.9	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	1	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	2	< 1	1	1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	1	1	0.9	2	2	2	2	0.9	1	0.9	2	1	2	1	0.9
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	2	< 0.9	4	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	9/12	/2019	9/11/	2019		9/10/2019		9/9/	2019	9/6/	2019	9/4/	2019	9/3/	2019	8/30	0/2019
	Location ID	FD01	FD02	FD01	FD02	F	D01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24		24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	ENE/2.2	mph/83°F	SW/4.7 i	nph/90°F		SE/3.4 mph/78°F		E/2.4 n	ph/82°F	E/4.3 m	nph/67°F	SSW/4.7	mph/90°F	E/2.2 m	ph/85°F	SW/4.7	mph/88°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS	NS	< 0.0089	NS	NS	NS	NS	NS	NS	< 0.0089	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	1	< 1	< 1	< 1	< 1	1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	1	< 0.6	1	< 0.6	< 0.6	0.8	2	0.8	< 0.6	2	< 0.6	< 0.6	< 0.6	< 0.6	0.7	0.8
Ethylbenzene	14.6	< 0.9	2	1	< 0.9	< 0.9	< 0.9	< 0.9	1	< 0.9	< 0.9	1	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	5	2	4	1	1	< 1	< 1	2	< 1	5	< 1	< 1	< 1	< 1	< 1	1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	3	0.9	1	< 0.8	< 0.8	0.9	3	2	< 0.8	2	< 0.8	< 0.8	0.8	0.9	1	1
Xylenes, Total	104	< 0.9	5	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	4	< 0.9	< 0.9	4	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)

> - below analytical reporting limit (shown).

Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	8/29	/2019	8/28	/2019		8/27/2019		8/26	6/2019	8/23	/2019		8/22/2019		8/21	1/2019
	Location ID	FD01	FD02	FD01	FD02	FI	D01	FD02	FD01	FD02	FD01	FD02	FD01	FI	D02	FD01	FD02
	Sample Exposure Time	24	24	24	24	:	24	24	24	24	24	24	24		24	24	24
	Average Wind Dir/Speed/Temp	NW/3.5	mph/83°F	E/2.4 m	ph/75°F		SE/3.5 mph/76°F		E/3.4 r	mph/77°F	N/1.9 n	ph/76°F		W/4.1 mph/91°F		SSW/4.0	mph/88°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	< 0.0089	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	1	1	0.9	0.8	0.9	0.9	< 0.8	< 0.8	1	0.9	< 0.8	< 0.8	< 0.8	0.9	1
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	8/20/	2019	8/19/	/2019		8/16/2019			8/15/2019		8/14/	2019		8/13/2019		8/12	2/2019
	Location ID	FD01	FD02	FD01	FD02	F	001	FD02	FC	01	FD02	FD01	FD02	FD01	F	002	FD01	FD02
	Sample Exposure Time	24	24	24	24	2	4	24	2	4	24	24	24	24	2	14	24	24
	Average Wind Dir/Speed/Temp	ESE/2.6	mph/89°F	S/4.0 m	ph/90°F		ESE/2.2 mph/82°F			ESE/3.5 mph/86°F		ENE/3.0	mph/87°F		SSW/2.6 mph/81°F		WSW/4.3	3 mph/87°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	< 0.0090	NS	NS	NS	NS	NS	NS	< 0.0089	< 0.0089	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	NS	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.7	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	NS	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.9	0.9	1	1	0.9	0.9	0.9	< 0.8	NS	< 0.8	1	1	1	1	1	1	1
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	NS	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		8/9/2019		8/8/	2019	8/7/	2019	8/6/	2019	8/5/	2019	8/2/	2019	8/1/	2019
	Location ID	FD01	FE	002	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	2	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp		WNW/4.2 mph/83°l	F	SSW/4.6	mph/87°F	S/5.0 n	nph/84°F	ESE/3.6	mph/81°F	E/2.7 n	nph/85°F	ESE/2.8	mph/87°F	E/2.7 m	iph/88°F
	Sample Type	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0086	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	12	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	2	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.7	1
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	1	< 1	1	< 1	1	1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	1	1	1	2	0.9	1	0.9	0.9	1	1	1	1	1	2
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	2

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		7/31/2019			7/30/2019			7/29/2019		7/26	/2019	7/25	/2019	7/24	2019	7/23	3/2019
	Location ID	FD01	FC	002	FD01	FI	D02	FD01	F	002	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	2	24	24		24	24	2	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp		SSW/3.1 mph/90°F			S/4.7 mph/92°F			SSW/4.2 mph/93°F		ESE/2.8	mph/89°F	ENE/3.1	mph/87°F	ENE/2.7	mph/86°F	NNE/3.1	mph/76°F
	Sample Type	Primary	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS	< 0.0087	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0086	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	1	1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	49	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	7	< 1	< 1	< 1
Benzene	4.68	2	2	2	< 0.6	< 0.6	< 0.6	0.9	1	0.6	0.7	< 0.6	0.7	0.8	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	1	1	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	1	6	7	< 1	1	2	7	7	< 1	3	3	< 1	4	< 1	2	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	1	< 1	1	< 1
Toluene	5,210	2	3	3	1	1	1	2	2	1	2	1	2	2	2	2	1	0.9
Xylenes, Total	104	< 0.9	4	3	< 0.9	< 0.9	< 0.9	< 0.9	2	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)

> - below analytical reporting limit (shown).

Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	7/22	/2019		7/19/2019		7/18	/2019	7/17	2019	7/16	/2019		7/15/2019			7/12/2019	
	Location ID	FD01	FD02	FD	001	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FE	002	FD01	F	D02
	Sample Exposure Time	24	24	2	24	24	24	24	24	24	24	24	24	2	4	24	2	24
	Average Wind Dir/Speed/Temp	SE/4.9 r	nph/90°F		S/4.1 mph/90°F		ENE/1.7	mph/80°F	SSW/4.2	mph/94°F	SW/4.4	mph/92°F		WNW/3.6 mph/88°I			WNW/5.5 mph/88°	F
	Sample Type	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Duplicate
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	0.01	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	1	< 1	1	< 1	< 1	1	< 1	1	< 1	1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	1	1	1	1	1	1	1	2	1	1	1	1	1	0.8	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	7/11	/2019		7/10/2019		7/9/	2019		7/8/2019		7/3/:	2019		7/2/2019	
	Location ID	FD01	FD02	FD01	F	002	FD01	FD02	F	001	FD02	FD01	FD02	FD01	F	D02
	Sample Exposure Time	24	24	24	2	24	24	24	2	24	24	24	24	24	2	24
	Average Wind Dir/Speed/Temp	SSE/5.6	mph/86°F		W/3.6 mph/91°F		NW/3.4	mph/89°F		E/2.1 mph/80°F		E/2.2 m	ph/90°F		W/3.7 mph/89°F	
	Sample Type	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	Duplicate
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	NS	NS	< 0.0088	NS	NS	NS	NS	NS	NS	NS	NS	NS	< 0.0086	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	<1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.7	0.7	0.8	0.8	< 0.6	1	0.8	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	0.9	< 0.9	< 0.9	< 0.9	< 0.9	0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	1	< 1	3	< 1	< 1	1	1	1	2	< 1	5	< 1	1	1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.9	1	1	0.9	0.9	2	3	2	2	1	3	2	1	1	1
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	3	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		7/1/2019		6/20	/2019		6/07	/2019			6/26/2019			6/25/2019	
	Sample Date		7/1/2019													
	Location ID	FD01	FD	002	FD01	FD02	F	D01	F	002	FD01	FI	002	F	001	FD02
	Sample Exposure Time	24	2	24	24	24	2	24	2	24	24		24	2	24	24
	Average Wind Dir/Speed/Temp		NNE/3.7 mph/90°F		ESE/2.8	mph/95°F		NW/4.4	mph/91°F			WNW/3.2 mph/91°	F		S/3.1 mph/86°F	
	Sample Type	Primary	Primary	Duplicate	Primary	Primary	Primary	Duplicate	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Duplicate	Primary
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	NS	NS	NS	NS	NS	< 0.0088	< 0.0088	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	NS	< 0.6	< 0.6	2	< 0.6	< 0.6	1	1	0.9
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	NS	< 0.9	< 0.9	1	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	2	< 1	4	< 1	< 1	NS	2	1	3	1	1	2	2	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	0.8	0.8	0.8	1	1	2	NS	1	1	2	1	1	2	2	2
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	NS	< 0.9	< 0.9	4	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	6/24	1/2019	6/21	/2019		6/20/2019			6/19/2019			6/18/2019			6/17/2019	
	Location ID	FD01	FD02	FD01	FD02	FI	D01	FD02	FI	D01	FD02	FC	001	FD02	FD01	F	D02
	Sample Exposure Time	24	24	24	24		24	24	:	24	24	2	24	24	24	2	24
	Average Wind Dir/Speed/Temp	SSW/3.3	mph/86°F	NNW/4.7	mph/80°F		E/1.6 mph/82°F			ESE/2.8 mph/73°F			SSE/1.9 mph/75°F			ENE/1.9 mph/77°F	
	Sample Type	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Primary	Primary	Duplicate
Analyte	Risk Screening Level																
	24-hour exposure																
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	< 0.0085	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	2	< 0.6	< 0.6	< 0.6	0.9	0.9	1	< 0.6	< 0.6	< 0.6	0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	2	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	4	< 1	1	< 1	1	< 1	< 1	1	< 1	< 1	1	< 1	< 1	1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1
Toluene	5,210	3	1	1	1	2	2	3	2	1	4	2	2	2	1	1	1
Xylenes, Total	104	4	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	3	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	6/14	/2019	6/13	/2019	6/12	/2019	6/11/2019		6/10/2019			6/7/2019		6/6/	/2019
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	F	001	FD02	FI	D01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	2	24	24	2	24	24	24	24
	Average Wind Dir/Speed/Temp	WSW/5.6	mph/72°F	ENE/5.4	mph/67°F	ESE/3.5	mph/77°F	NW/7.1 mph/78°F		E/4.6 mph/67°F			E/2.4 mph/84°F		NNW/4.3	mph/85°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Duplicate	Primary	Primary	Primary
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	NS	NS	NS	NS	NS	NS	< 0.0088	NS	NS	NS	NS	NS	NS	< 0.0085	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	0.7	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	NS	0.7	0.7	0.7	1	1	0.7	1	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	1	NS	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	1	< 1	1	< 1	2	< 1	NS	1	< 1	< 1	4	4	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	NS	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	1	1	0.9	1	1	NS	2	2	2	2	2	2	1	2
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	NS	3	2	< 0.9	3	2	< 0.9	< 0.9	2

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		6/5/2019		6/4/	2019	6/3/	2019	5/31	2019	5/30	/2019	5/29/	/2019	5/28/	2019	5/21	/2019
	Location ID	FD01	F	002	FD01	FD02												
	Sample Exposure Time	24	2	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp		S/4.0 mph/82°F		WSW/4.5	mph/72°F	WNW/5.9	mph/72°F	WNW/4.1	mph/81°F	SSE/3.4	mph/70°F	E/3.5 m	iph/70°F	ESE/4.5	mph/68°F	NW/7.8	mph/72°F
	Sample Type	Primary	Primary	Duplicate	Primary	Primary												
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	0.7	< 0.6	< 0.6	1	0.7	0.7	2	0.7	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.7	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	1	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	3	< 1	< 1	6	3	< 1	6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	1	1	1	2	1	1	3	1	1	2	2	1	1	< 0.8	2	< 0.8	< 0.8
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	3	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

# Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	5/20	/2019	5/16	/2019	5/15	/2019	5/14	/2019	5/13	3/2019	5/10/2019	5/9/	2019	5/8/	/2019
	Location ID	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD01	FD02	FD02	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
	Average Wind Dir/Speed/Temp	SW/5.6	mph/88°F	WNW/4.0	mph/74°F	NW/5.2	mph/70°F	E/1.7 m	ph/51°F	E/5.2 n	nph/49°F	SSE/3.4 mph/72°F	ESE/5.2	mph/61°F	E/2.8 m	nph/71°F
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level															
	24-hour exposure															
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Benzene	4.68	< 0.6	< 0.6	0.7	0.7	< 0.6	< 0.6	0.7	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Toluene	5,210	< 0.8	< 0.8	2	2	1	0.9	2	1	< 0.8	< 0.8	1	< 0.8	0.9	1	1
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)

> - below analytical reporting limit (shown).

Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date		5/7/2019 5/6/201		2019	19 5/2/2019			5/1/2019		4/30/2019			4/29/2019		4/25/2019		
	Location ID	FD01	FD02	FD01	FD02	FD01	FE	002	FD01	FD02	FI	D01	FD02	FD01	FD02	FD01	FD02	
	Sample Exposure Time	24	24	24	24	24	2	24	24	24	:	24	24	24	24	24	24	
	Average Wind Dir/Speed/Temp	SSE/4.2 mph/69°F		E/3.1 mph/74°F		SE/2.9 mph/78°F			SE/4.9 mph/55°F		ESE/1.9 mph/61°F		SE/3.0 r		mph/59°F SI		/2.9 mph/63°F	
	Sample Type	Primary	Primary	Primary	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Duplicate	Primary	Primary	Primary	Primary	Primary	
Analyte	Risk Screening Level																	
	24-hour exposure																	
Arsenic	0.037	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	
Benzene	4.68	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	0.7	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	< 0.6	
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	
Isopropylbenzene	417	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	
Naphthalene	3.13	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	<1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	
Toluene	5,210	2	1	1	1	1	1	1	26 E	1	1	1	1	< 0.8	< 0.8	1	1	
Xylenes, Total	104	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	< 0.9	

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.

Perimeter Locations

Edgewater, New Jersey

	Sample Date	4/24/	/2019	4/23/	2019
	Location ID	FD01	FD02	FD01	FD02
	Sample Exposure Time	24	24	24	24
	Average Wind Dir/Speed/Temp	NW/7.9 i	mph/68°F	S/3.7 m	ph/75°F
	Sample Type	Primary	Primary	Primary	Primary
Analyte	Risk Screening Level				
	24-hour exposure				
Arsenic	0.037	NS	NS	NS	NS
1,2,4-Trimethylbenzene	62.6	< 1	< 1	< 1	< 1
1,3,5-Trimethybenzene	62.6	< 1	< 1	< 1	< 1
Benzene	4.68	2	0.7	0.7	0.6
Ethylbenzene	14.6	< 0.9	< 0.9	< 0.9	< 0.9
Isopropylbenzene	417	< 1	< 1	< 1	< 1
Naphthalene	3.13	< 1	< 1	< 1	< 1
n-Propylbenzene	1,040	< 1	< 1	< 1	< 1
Toluene	5,210	5	0.8	2	1
Xylenes, Total	104	2	< 0.9	< 0.9	< 0.9

## Notes:

All data shown in micrograms per cubic meter (µg/m³)
> - below analytical reporting limit (shown).
Average wind direction/speed/temperature measured at a sensor on the Quanta Property

Levels in air that are shaded are greater than the applicable RSL. The RSL is used principally as a screening value used to guide actions at the site to control emissions and odors. The RSL was calculated using a scenario assuming an individual stands on the site perimeter for 24 hours per day for 2 years.